

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Acquired Wastewater Technologies, LLC	Alliance	500	500
Acquired Wastewater Technologies, LLC	Cajun Aire Advanced	500	500, 750
Acquired Wastewater Technologies, LLC	Cajun Aire Basic	500	500, 750
Aero-Tech	Aero-Tech	AT-500	AT-500, AT-600, AT-750, AT-1000, AT-1500
American Wastewater Systems, Inc.	B.E.S.T. 1 AWS 500	500	B.E.S.T.1 AWS-500, 800, 1000, 1200
Anua	Puraflo P150N	Puraflo P150N*3B	P150N*3B, P150N*4B, P150N*5B, P150N*6B, P150N*7B, P150N*8B, P150N*9B, P150N*10B
Anua	PuraSys	PekaSys CRB1 (PuraSys PS1-4)	PS1-5, PS1-6, PS1-7, PS1-8, PS1-9, PS1-10, PS1-11, PS1-12, PS1-13, and PS1-14
Aquaklear, Inc.	AquaKlear	AK6PT	AK6PTC, AK10PTC
Aquaklear, Inc.	AquaKlear	AK6S	AK6S245C AK10S245C, AK6S245F
Aquaklear, Inc.	AquaKlear	AK500C	AK500C/F, AK600F, AK750C/F, AK800CA/F, AK1000C/F, AK1500F
Bio-Microbics, Inc.	BioBarrier	MBR 0.5	MBR 0.5, 0.5-N, 1.0, 1.0-N, 1.5, 1.5-N
Bio-Microbics, Inc.	MicroFAST ¹	0.5	MicroFast 0.5, 0.625, 0.75, 0.9, 1.5 ¹
Bionest Technologies	Bionest	BN-400	BNC-400, BNC-500, BNC-600, BNC-750, BNC-1000, BNC-1250 and BNC-1500
Clearstream Wastewater Systems, Inc.	Clearstream	500 N	500N, 600N, 600NC3T, 750N, 1000N, 1500N.
Clearstream Wastewater Systems, Inc.	Clearstream	500 D	500D, 500DT, 500DST, 600D, 600DT, 600DC3, 750D, 750DT, 800D, 1000D, 1000DT, 1500D

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a related capacity of 750 gpd or 800 gpd

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.

Disclaimer: This list does not represent or imply an endorsement of any particular company, person, product, configuration, or technology. The list reflects the compiler’s information as of June 6, 2022

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Clearstream Wastewater Systems, Inc.	Clearstream	500 DA	500DA, 500DAT, 500DAST, 600DA, 600DAT, 600DAC3, 800DA
Consolidated Treatment Systems	Enviro-Guard	Enviro-Guard-ENV-0.75	Enviro-Guard-ENV-0.75
Consolidated Treatment Systems	Multi-Flo	FTB-0.5	FTB 0.5, 0.6,.75, 1.0, 1.5
Consolidated Treatment Systems	Nayadic	M-6A	M-6A, 8A, 1050A, 1200A, 2000A
Delta Treatment Systems, LLC.	Delta DF	DF40-M	DF50-FF, DF50-CA, DF60-FF, DF-75-FF, DF100-FF, DF150-FF
Delta Treatment Systems, LLC.	Delta UC	UC50	UC50-FF, UC50-CA, UC60-FF, UC-75-FF, UC100-FF, UC150-FF
Delta Treatment Systems, LLC	ECOPOD-N	E50-N	E50-N, E-50-N-IM1060, E-60-N E-60-N-IM1060, E75-N, E-75-N-IM1060, E100-N, and E-100-N-IM1530
Delta Treatment Systems, LLC	Enviro-Aire	EA50	EA 52.5, EA 75
Ecological Tanks, Inc.	Aqua Aire	500	AA500-C, AA600-C, AA800-C, AA1000-C, AA1200-C
Ecological Tanks, Inc.	Aqua Safe	500	AS500-F, AS600-F, AS750-F, AS1000-F, AS1500-F
Fuji Clean USA	CE	5	CE 5, 7, 10, 14
Fuji Clean USA	CEN	5	CEN 5, 7, 10, 14
Hoot Systems LLC	HOOT	H-500 A	H-500 A, 750A, 1000A
Hoot Systems LLC	HOOT	H-600 A	H-600A
Hoot Systems LLC	HOOT	ANR 450	Hoot ANR-450
Hydro-Action Industries	Hydro-Action	AP500	AP-500, 600, 750, 1000G, 1500G

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a related capacity of 750 gpd or 800 gpd

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Jet Inc.	Jet	J-500 (Model J-353)	J-500, J-600, J-750, J-1000, J-1250, J-1500
Jet Inc.	Jet	J-500CF	J-500CF, J-750CF, J-1000CF, J-1250CF, J-1500CF
Norweco, Inc.	Singulair TNT	TNT-500	Singulair TNT-500 ² , Singulair Green TNT-500 ² , Singulair TNT-750 ³ , Singulair TNT-1000, Singulair TNT-1250, T Singulair TNT-1500
Norweco, Inc.	Singulair 960	960 w/ Biokinetics 500	Singulair 960-500GPD System ² , Singulair Green 960 500GPD System ² , Singulair 960-750GPD ³ System, Singulair 960-1000GPD System, Singulair 960-1250GPD System, Singulair 960-1500GPD System;
Orengo Systems	Advantex	AX20N (Mode 1)	AX20N, AX20RT
Premier Tech Environment	Ecoflo Biofilter	STB-500	STB-650
Presby Environmental, Inc.	Advanced Enviro-Septic	Simple Septic (used to certify Advanced Enviro-Septic)	NSF 40-certified models not currently marketed or sold in Florida
Quanics	Aerocell	ATS SCAT-8-AC-C500	ATS SCAT-AC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050
Quanics	Bio-Coir	ATS-SCAT-8-BC-C500	ATS SCAT-BC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a related capacity of 750 gpd or 800 gpd

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.