

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

| Manufacturer | Equipment Series | NSF 40 Tested Model | Florida-Approved NSF 40-Certified Models |
|--|-------------------------|------------------------------|---|
| Acquired Wastewater Technologies, LLC | Alliance | 500 | 500 |
| Acquired Wastewater Technologies, LLC | Cajun Aire Advanced | 500 | 500, 750 |
| Acquired Wastewater Technologies, LLC | Cajun Aire Basic | 500 | 500, 750 |
| Aero-Tech | Aero-Tech | AT-500 | AT-500, AT-600, AT-750, AT-1000, AT-1500 |
| American Wastewater Systems, Inc. | B.E.S.T. 1 AWS 500 | 500 | B.E.S.T.1 AWS-500, 800, 1000, 1200 |
| Anua | Puraflo P150N | Puraflo P150N*3B | P150N*3B, P150N*4B, P150N*5B, P150N*6B, P150N*7B, P150N*8B, P150N*9B, P150N*10B |
| Anua | PuraSys | PekaSys CRB1 (PuraSys PS1-4) | PS1-5, PS1-6, PS1-7, PS1-8, PS1-9, PS1-10, PS1-11, PS1-12, PS1-13, and PS1-14 |
| Aquaklear, Inc. | AquaKlear | AK6PT | AK6PTC, AK10PTC |
| Aquaklear, Inc. | AquaKlear | AK6S | AK6S245C AK10S245C, AK6S245F |
| Aquaklear, Inc. | AquaKlear | AK500C | AK500C/F, AK600F, AK750C/F, AK800CA/F, AK1000C/F, AK1500F |
| Bio-Microbics, Inc. | BioBarrier | MBR 0.5 | MBR 0.5, 0.5-N, 1.0, 1.0-N, 1.5, 1.5-N |
| Bio-Microbics, Inc. | MicroFAST ¹ | 0.5 | MicroFast 0.5, 0.625, 0.75, 0.9, 1.5 ¹ |
| Bionest Technologies | Bionest | BN-400 | BNC-400, BNC-500, BNC-600, BNC-750, BNC-1000, BNC-1250 and BNC-1500 |
| Clearstream Wastewater Systems, Inc. | Clearstream | 500 N | 500N, 600N, 600NC3T, 750N, 1000N, 1500N. |
| Clearstream Wastewater Systems, Inc. | Clearstream | 500 D | 500D, 500DT, 500DST, 600D, 600DT, 600DC3, 750D, 750DT, 800D, 1000D, 1000DT, 1500D |

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.

Disclaimer: This list does not represent or imply an endorsement of any particular company, person, product, configuration, or technology. The list reflects the compiler’s information as of January 31, 2023.

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

| Manufacturer | Equipment Series | NSF 40 Tested Model | Florida-Approved NSF 40-Certified Models |
|--------------------------------------|------------------|-----------------------|--|
| Clearstream Wastewater Systems, Inc. | Clearstream | 500 DA | 500DA, 500DAT, 500DAST, 600DA, 600DAT, 600DAC3, 800DA |
| Consolidated Treatment Systems | Enviro-Guard | Enviro-Guard-ENV-0.75 | Enviro-Guard-ENV-0.75 |
| Consolidated Treatment Systems | Multi-Flo | FTB-0.5 | FTB 0.5, 0.6, .75, 1.0, 1.5 |
| Consolidated Treatment Systems | Nayadic | M-6A | M-6A, 8A, 1050A, 1200A, 2000A |
| Delta Treatment Systems, LLC. | Delta DF | DF40-M | DF50-FF, DF50-CA, DF60-FF, DF-75-FF, DF100-FF, DF150-FF |
| Delta Treatment Systems, LLC. | Delta UC | UC50 | UC50-FF, UC50-CA, UC60-FF, UC-75-FF, UC100-FF, UC150-FF |
| Delta Treatment Systems, LLC | ECOPOD-N | E50-N | E50-N, E-50-N-IM1060, E-60-N E-60-N-IM1060, E75-N, E-75-N-IM1060, E100-N, and E-100-N-IM1530 |
| Delta Treatment Systems, LLC | Enviro-Aire | EA50 | EA 52.5, EA 75 |
| Ecological Tanks, Inc. | Aqua Aire | 500 | AA500-C, AA600-C, AA800-C, AA1000-C, AA1200-C |
| Ecological Tanks, Inc. | Aqua Safe | 500 | AS500-F, AS600-F, AS750-F, AS1000-F, AS1500-F |
| Fuji Clean USA | CE | 5 | CE 5, 7, 10, 14 |
| Fuji Clean USA | CEN | 5 | CEN 5, 7, 10, 14 |
| Hoot Systems LLC | HOOT | H-500 A | H-500 A, 750A, 1000A |
| Hoot Systems LLC | HOOT | H-600 A | H-600A |
| Hoot Systems LLC | HOOT | ANR 450 | Hoot ANR-450 |
| Hydro-Action Industries | Hydro-Action | AP500 | AP-500, 600, 750, 1000G, 1500G |

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.

NSF Standard 40 Certified Aerobic Treatment Units (ATUs) in Florida

(Rule 62-6.012, Florida Administrative Code)

| Manufacturer | Equipment Series | NSF 40 Tested Model | Florida-Approved NSF 40-Certified Models |
|-----------------------------------|-------------------------|--|---|
| Jet Inc. | Jet | J-500 (Model J-353) | J-500, J-600, J-750, J-1000, J-1250, J-1500 |
| Jet Inc. | Jet | J-500CF | J-500CF, J-750CF, J-1000CF, J-1250CF, J-1500CF |
| Norweco, Inc. | Singulair TNT | TNT-500 | Singulair TNT-500 ² , Singulair Green TNT-500 ² , Singulair TNT-750 ³ , Singulair TNT-1000, Singulair TNT-1250, T Singulair TNT-1500 |
| Norweco, Inc. | Singulair 960 | 960 w/ Biokinetics 500 | Singulair 960-500GPD System ² , Singulair Green 960 500GPD System ² , Singulair 960-750GPD ³ System, Singulair 960-1000GPD System, Singulair 960-1250GPD System, Singulair 960-1500GPD System; |
| Orenco Systems | Advantex | AX20N (Mode 1) | AX20N, AX20RT |
| Premier Tech Environment | Ecoflo Biofilter | STB-500 | STB-650 |
| Presby Environmental, Inc. | Advanced Enviro-Septic | Simple Septic (used to certify Advanced Enviro-Septic) | NSF 40-certified models not currently marketed or sold in Florida |
| Quanics | Aerocell | ATS SCAT-8-AC-C500 | ATS SCAT-AC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050 |
| Quanics | Bio-Coir | ATS-SCAT-8-BC-C500 | ATS SCAT-BC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050 |

¹ See remarks in tank listings [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#) for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: [Tanks - Approved for use with Aerobic Treatment Units \(ATUs\)](#). Be aware that the model identification in that list is not always complete.