Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Acquired Wastewater Technologies, LLC	Alliance	500	500
Acquired Wastewater Technologies, LLC	Cajun Aire Advanced	500	500, 750
Acquired Wastewater Technologies, LLC	Cajun Aire Basic	500	500, 750
Aero-Tech	Aero-Tech	AT-500	AT-500, AT-600, AT-750, AT-1000, AT-1500
American Wastewater Systems, Inc.	B.E.S.T. 1 AWS 500	500	B.E.S.T.1 AWS-500, 800, 1000, 1200
Anua	Puraflo P150N	Puraflo P150N*3B	P150N*3B, P150N*4B, P150N*5B, P150N*6B, P150N*7B, P150N*8B, P150N*9B, P150N*10B
Anua	PuraSys	PekaSys CRB1 (PuraSys PS1-4)	PS1-5, PS1-6, PS1-7. PS1-8, PS1-9, PS1-10, PS1-11, PS1-12, PS1-13, and PS1-14
Aquaklear, Inc.	AquaKlear	AK6PT	AK6PTC, AK10PTC
Aquaklear, Inc.	AquaKlear	AK6S	AK6S245C AK10S245C, AK6S245F
Aquaklear, Inc.	AquaKlear	AK500C	AK500C/F, AK600F, AK750C/F, AK800CA/F, AK1000C/F, AK1500F
Bio-Microbics, Inc.	BioBarrier	MBR 0.5	MBR 0.5, 0.5-N, 1.0, 1.0-N, 1.5, 1.5-N
Bio-Microbics, Inc.	MicroFAST ¹	0.5	MicroFast 0.5, 0.625, 0.75, 0.9, 1.5 ¹
Bionest Technologies	Bionest	BN-400	BNC-400, BNC-500, BNC-600, BNC-750, BNC-1000, BNC-1250 and BNC-1500
Clearstream Wastewater Systems, Inc.	Clearstream	500 N	500N, 600N, 600NC3T, 750N, 1000N, 1500N.
Clearstream Wastewater Systems, Inc.	Clearstream	500 D	500D, 500DT, 500DST, 600D, 600DT, 600DC3, 750D, 750DT, 800D, 1000D, 1000DT, 1500D

¹ See remarks in tank listings <u>Tanks - Approved for use with Aerobic Treatment Units (ATUs)</u> for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: <u>Tanks</u>

- <u>Approved for use with Aerobic Treatment Units (ATUs)</u>. Be aware that the model identification in that list is not always complete.

Disclaimer: This list does not represent or imply an endorsement of any particular company, person, product, configuration, or technology. The list reflects the compiler's information as of June 10, 2024.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.

Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Clearstream Wastewater Systems, Inc.	Clearstream	500 DA	500DA, 500DAT, 500DAST, 600DA, 600DAT, 600DAC3, 800DA
Consolidated Treatment Systems	Enviro-Guard	Enviro-Guard- ENV-0.75	Enviro-Guard-ENV-0.75
Consolidated Treatment Systems	Multi-Flo	FTB-0.5	FTB 0.5, 0.6,.75, 1.0, 1.5
Consolidated Treatment Systems	Nayadic	M-6A	M-6A, 8A, 1050A, 1200A, 2000A
Delta Treatment Systems, LLC.	Delta DF	DF40-M	DF50-FF, DF50-CA, DF60-FF, DF-75-FF, DF100-FF, DF150-FF
Delta Treatment Systems, LLC.	Delta UC	UC50	UC50-FF, UC50-CA, UC60-FF, UC-75-FF, UC100-FF, UC150-FF
Delta Treatment Systems, LLC	ECOPOD-N	E50-N	E50-N, E-50-N-IM1060, E-60-N E-60-N-IM1060, E75-N, E-75-N-IM1060, E100-N, and E-100-N-IM1530
Delta Treatment Systems, LLC	ECOPOD-NR	E50-NR	E50-NR
Delta Treatment Systems, LLC	ECOPOD-NX	E50-NX	E50-NX
Delta Treatment Systems, LLC	Enviro-Aire	EA50	EA 52.5, EA 75
Ecological Tanks, Inc.	Aqua Aire	500	AA500-C, AA600-C, AA800-C, AA1000-C, AA1200-C
Ecological Tanks, Inc.	Aqua Safe	500	AS500-F, AS600-F, AS750-F, AS1000-F, AS1500-F
Fuji Clean USA	CE	5	CE 5, 7, 10, 14
Fuji Clean USA	CEN	5	CEN 5, 7, 10, 14
Hoot Systems LLC	HOOT	H-500 A	H-500 A, 750A, 1000A
Hoot Systems LLC	НООТ	H-600 A	H-600A
Hoot Systems LLC	НООТ	ANR 450	Hoot ANR-450
Hoot Systems LLC	НООТ	ANR 500	Hoot ANR-500
Hydro-Action Industries	Hydro-Action	AP500	AP-500, 600, 750, 1000G, 1500G

¹ See remarks in tank listings <u>Tanks - Approved for use with Aerobic Treatment Units (ATUs)</u> for information on pretreatment tank sizing required for NSF 40 and 245 certification when the unit Microfast is housed in a single compartment tank.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: <u>Tanks</u> - <u>Approved for use with Aerobic Treatment Units (ATUs)</u>. Be aware that the model identification in that list is not always complete.

Disclaimer: This list does not represent or imply an endorsement of any particular company, person, product, configuration, or technology. The list reflects the compiler's information as of June 10, 2024.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.

Manufacturer	Equipment Series	NSF 40 Tested Model	Florida-Approved NSF 40-Certified Models
Jet Inc.	Jet	J-500 (Model J-353)	J-500, J-600, J-750, J-1000, J-1250, J-1500
Jet Inc.	Jet	J-500CF	J-500CF, J-750CF, J-1000CF, J-1250CF, J-1500CF
Norweco, Inc.	Singulair TNT	TNT-500	Singulair TNT-500 ² , Singulair Green TNT-500 ² , Singulair TNT-750 ³ , Singulair TNT-1000, Singulair TNT-1250, T Singulair TNT-1500
Norweco, Inc.	Singulair 960	960 w/ Biokinetics 500	Singulair 960-500GPD System ² , Singulair Green 960 500GPD System ² , Singulair 960-750GPD ³ System, Singulair 960-1000GPD System, Singulair 960-1250GPD System, Singulair 960-1500GPD System;
Orenco Systems	Advantex	AX20N (Mode 1)	AX20N, AX20RT
Premier Tech Environment	Ecoflo Biofilter	STB-500	STB-650
Presby Environmental, Inc.	Advanced Enviro- Septic	Simple Septic (used to certify Advanced Enviro-Septic)	NSF 40-certified models not currently marketed or sold in Florida
Quanics	Aerocell	ATS SCAT-8- AC-C500	ATS SCAT-AC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050
Quanics	Bio-Coir	ATS-SCAT-8- BC-C500	ATS SCAT-BC-200, ATS SCAT-400, ATS SCAT-650 ATS SCAT-1050

¹ See remarks in tank listings <u>Tanks - Approved for use with Aerobic Treatment Units (ATUs)</u> for information on pretreatment tank sizing required for NSF 245 certification when the unit Microfast is housed in a single compartment tank.

Please note that Florida requires approval of treatment receptacles prior to sale and installations. A list of approved treatment receptacles for use with ATUs can be found at: <u>Tanks</u> - <u>Approved for use with Aerobic Treatment Units (ATUs)</u>. Be aware that the model identification in that list is not always complete.

Disclaimer: This list does not represent or imply an endorsement of any particular company, person, product, configuration, or technology. The list reflects the compiler's information as of June 10, 2024.

² Norweco Singulair 960 and TNT-500 GPD are NSF 40 certified for a rated treatment capacity of 500 gpd or 600 gpd.

³ Norweco Singulair 960 and TNT-750 GPD are NSF 40 certified for a rated treatment capacity of 750 gpd or 800 gpd.